Galassia

Floor Lamp | 220-240 V | 6xE14 9560



Technical data	
Technical data	
Construction year	2021
Туре	Floor Lamp
Installation position	Floor
Installation environment	Indoor
Power	6 x 6 W
Lamp cap	6 x E14
Frequency	50-60 Hz
Optics	General Lighting
Light emission direction	downward and upward
Safety class	1
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	3.5 m
Electric socket	Type F
Resin potting	No

$[\texttt{H} [\texttt{CC} \hspace{0.1cm} \underset{\texttt{AHS}}{\checkmark} \hspace{0.1cm} \overset{\texttt{A}}{\boxtimes} \hspace{0.1cm} \overset{\texttt{A}}{\cong} \hspace{0.1cm} \overset{\texttt{A}}{\boxtimes} \hspace{0.1cm} \overset{\texttt{A}}{\cong} \hspace{0.1cm} \overset{\texttt{A}}{\cong} \hspace{0.1cm} \overset{\texttt{A}}{\boxtimes} \hspace{0.1cm} \overset{\texttt{A}}{\boxtimes} \hspace{0.1cm$



Finishing casin	g	
Material	Brass	
Colour	gold	
Processing	Electroplating	

Finishing diffuser		
Material	Glass	
Colour	white	

Galassia

Floor Lamp | 220-240 V | 6xE14 9560

Double emission floor lamp for indoor application. LED lamplamp included, lamp cap 6xE14.

The device body is made of brass and features a gold finish, processed by means of electroplating; the diffuser is made of glass. The ingress protection degree is IP20;

. The power supply cable is included and features a 3.5 m lenght.

The device features protection class I and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features		
Source lumens	4836 lm	
Colour temperature	2700 K	
Junction temperature (lighting fixture)	80	
Standard Operating Ambient Temperature	25	