

Callimaco LED 2700K



IP20 🗆 🕅 🞯

TECHNICAL DRAWINGS



DESIGN BY

Ettore Sottsass

DESCRIPTION

Base and diffuser in painted steel, stem in painted aluminium, handle in polished chrome metal plate. Indirect light emission. Colour: multicolour.

A0111W00 Multicolour	Material: Series:	Aluminium, steel
	Series [.]	D .
	501105.	Design
Floor	Area contract:	Residential
Indoor	Emission:	Indirect
cm 200	Glow Wire Test:	650
S		
LED	Color temperature (K):	2700K
1	Color Tolerance:	MacAdam 2SDCN
36.36W	CRI:	90
ut (lm): 3646lm	Efficacy:	100lm/W
0	Service Life:	50000-L70
A		
43W	Delivered lumens output (lm):3225lm	
220V-240V	CCT:	2700K
	Efficiency:	92%
	Efficacy:	75.00lm/W
	CRI:	90
	cm 200 ED 1 36.36W ut (Im):3646Im 0 A 43W	cm 200 Glow Wire Test: S LED Color temperature (K): 1 Color Tolerance: 36.36W CRI: ut (Im):3646Im Efficacy: 0 Service Life: A 43W Delivered lumens output (220V-240V CCT: Efficiency: Efficacy:

Notes

LED included, with dimmer.